

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.



03 Co

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Applicant:

§
§

Shmuel Mangovi

§

Serial No.: 09/972,246

§

§

Filed: Oct. 9, 2001

§

Group Art Unit:

§

For: OPTICAL WINDOW ASSEMBLY
FOR USE IN A SUPERSONIC
PLATFORM

§

Attorney

§

Docket: 26/414

§

§

§

Examiner:

§

Commissioner of Patents and Trademarks
Washington, D.C. 20231

TRANSMITTAL LETTER


Sir:

The following document is enclosed:

- (1) Certified copy IL 139304.

✓

Respectfully submitted,



Mark M. Friedman
Attorney for Applicant
Registration No. 33,883

Date: November 26, 2001



מדינת ישראל
STATE OF ISRAEL

Ministry of Justice
Patent Office

משרד המשפטים
לשכת הפטנטים

This is to certify that annexed
hereto is a true copy of the
documents as originally
deposited with the patent
application of which
particulars are specified on the
first page of the annex.

זאת לתעודה כי רצופים
בזה העתקים נכונים של
המסמכים שהופקדו
לכתחילה עם הבקשה
לפטנט לפי הפרטים
הרשומים בעמוד הראשון
של הנספח.

21-11-2001
This _____ היום
ממונה על
רשם הפטנטים
Commissioner of Patents

נתאשר
Certified

לשימוש הלשכה
For Office Use

חוק הפטנטים, תשכ"ז - 1967
PATENT LAW, 5727 - 1967

ב ק ש ה ל פ ט נ ט
Application For Patent

139304	מספר : Number
26-10-2000	תאריך : Date
	הוקדם/נרחה Ante/Post-dated

אני, (שם המבקש, מענו ולגבי גוף מאוגד - מקום התאגדותו)
I (Name and address of applicant, and in case of body corporate - place of incorporation)

State Of Israel - Ministry Of Defense
Rafael - Armament Development Authority
P.O.Box 2250
Haifa 31021

מדינת ישראל - משרד הבטחון
רפא"ל - רשות פתוח אמצעי לחימה
ת.ד. 2250
חיפה 31021

ממציא : שמואל מנגובי

Inventor: Shmuel Mangovi

בעל אמצאה מכח הדין Operation of Law ששמה הוא
Owner, by virtue of
of an invention the title of which is

מתקן חלון אופטי לשימוש בפלטפורמה על-קולית



(בעברית)
(Hebrew)

OPTICAL WINDOW ASSEMBLY FOR USE IN A SUPERSONIC PLATFORM

(באנגלית)
(English)

hereby apply for a patent to be granted to me in respect thereof

מבקש בזאת כי ינתן לי עליה פטנט

• בקשת חלוקה - Application of Division		• בקשת פטנט מוסף - Application for Patent Addition		• דרישת דין קדימה Priority Claim	
מבקשת פטנט from Application		לבקשה/לפטנט to Patent/Appl.		מספר/סימן Number/Mark	תאריך Date
No. מס'		No. מס'			
dated מיום		dated מיום			
יפוי כח : כללי P.O.A.: general/individual-attached/to be filed later-					
הוגש בענין 109841 filed in case					
המען למסירת מכתבים בישראל Address for service in Israel DR. MARK FRIEDMAN LTD. BEIT SAMUELOFF 7 HAOMANIM STREET 67897 TEL AVIV					
חתימת המבקש Signature of Applicant				היום 25 בחודש Oct שנת 2000 This of of the year	
					

לשימוש הלשכה
For Office Use

Ref.: 26/292

מתקן חלון אופטי לשימוש בפלטפורמה על-קולית

OPTICAL WINDOW ASSEMBLY FOR USE IN A SUPERSONIC PLATFORM

OPTICAL WINDOW ASSEMBLY FOR USE IN A SUPERSONIC PLATFORM

FIELD AND BACKGROUND OF THE INVENTION

5 The present invention relates to an optical window or dome assembly configured for use high at high supersonic speeds and, more particularly, to an assembly which prevents excessive heating of heat sensitive components thereof, thereby preserving the optical properties thereof at high supersonic speeds. The invention further relates to a mobile platform equipped with such an assembly.

10 A typical guided missile is commonly made up of a number of sections, which are housed in, or connected to a generally cylindrical housing of varying radius in the longitudinal direction.

 In one type of a guided missile, at the front of the missile is the guidance section which typically includes one or more sensors, such as a Forward Looking
15 Infrared (FLIR) or video camera, and the various electronic systems which control the sensors, analyze and interpret the signals received by the sensors, and control the flight control system which positively determines the trajectory. The guidance section may also include means for receiving signals from outside of the missile and may also include means for transmitting signals from the missile.

20 Behind the guidance section of the missile is the warhead which is typically a hollow cylindrically shaped casing made of high strength steel. The function of the warhead is to place an explosive charge in the appropriate position at the moment of explosion, thereby maximizing the effect of the explosion on the target. Inside the hollow casing is placed the explosive and in the rear end of the warhead lies the
25 ignition fuse which is designed to be set off at the proper moment, typically, at some pre-determined time after the warhead encounters the target. The warhead is typically

made of three sections (i) a front section, or nose, which is usually in the shape of an ogive or cone; (ii) the main section which includes the explosive charge and is usually cylindrical; and (iii) the aft section which seals the explosive charge within the casing and holds the fuse.

5 Behind the warhead typically lies the engine which provides thrust to the missile.

Housed in and connected to the housing at the rear of the missile, and in some cases also in other locations along the missile housing, is the flight control section, including fins and foils, which are used to adjust and stabilize the trajectory of the
10 missile during its flight to the target.

There is often a necessity for a missile or rocket to fly at high supersonic speeds. Such a necessity may arise for a number of reasons. For example, a missile fired at a moving airplane, whether from another airplane or from a fixed position on the ground, must travel at a speed greater than that of the target airplane. The distance
15 between the launch point and the target airplane at the time of launch, together with the speed of the target airplane will determine the speed at which the missile must travel. Since modern warplanes typically fly at speeds in excess of Mach 1, there is a need for missiles which fly at far greater speeds, for example Mach 4 or Mach 5. Additionally, missiles fired at stationary targets which are heavily defended by
20 antimissile defense systems are most likely to reach the target if they fly at high supersonic speeds because this minimizes the time between detection and impact during which defensive measures may be taken.

Navigation of a guided missile to target must be conducted exclusively by a guidance system. One or more guidance systems are generally employed. Radar is one
25 such guidance system. Radar is effective, but is subject to interference, both

intentional interference deployed as defense mechanism, and accidental interference resulting from environmental conditions. Therefore, radar is often employed in conjunction with optical or electro-optical guidance systems, either of which may operate in the visible or infrared portion of the spectrum. These guidance systems are composed of a sensor or a detection system (e.g., electro-optical camera), and an analyzing system. The detection system must be onboard, although the analyzing system may be located outside the missile, for example at a base on the ground or in a platform such as an airplane which launched the missile, which communicates with the missile during flight. Alternatively, both the detection system and the analyzing system are carried on-board. This alternative, referred to as a "launch and forget" guidance system, is especially desirable in the case of missiles flying at high supersonic speeds where the time available for navigation decisions is extremely short, making communication with a remote location a practical impossibility.

The detection system must have a sensor in communication with the environment. At the same time, the sensor must be protected from the environment. For optical or electro-optical guidance systems this protection typically takes the form of an optical window or dome. These windows or domes are transparent to transmissions in a chosen range of wavelengths, while being opaque to transmissions with a wavelength outside that range. These optical windows or domes are typically coated with a shielding material which gives the window or dome the desired optical properties. As explained by D. Harris in "Materials for Infrared Windows and Domes (SPIE Optical Engineering Press, 1948), which is incorporated herein by reference, most common approaches to shielding include coating the optical window with an electrically conductive layer, covering the window with a metallic mesh, or increasing the conductivity of the material forming the window. In general, the thin electrically

conductive coatings applied to the window are transparent at visible and/or infrared frequencies, but opaque to microwaves and radio waves. This makes such coatings useful in shielding sensitive electro-optical detectors against harmful electromagnetic interference (Kohin et al., SPIE Crit. Rev. CR39: 3-34(1992)). The shielding capabilities of these materials stems from their ability to reflect and/or absorb incident radiation. In general, the greater the conductivity of the coating material, the more effective the shielding. Common coating materials are described in, for example, (i) Pellicori and Colton, Thin Solid Films 209: 109-115 (1992); (ii) Rudisill et al., Appl. Opt. 13: 2075-2080 (1974) and (iii) Bui and Hassan, Proc. SPIE 3060:2-10 (1997), all of which are incorporated herein by reference. Since the conductivity of these materials decreases with increasing temperature, they lose their shielding effectiveness when they are heated. At the same time, transmission of desired wavelengths through the shield is often diminished by heating.

Unfortunately, at high supersonic speeds (e.g., several mach), friction from the air causes heating of the optical window or dome, changing the conductivity of the coating and altering the optical properties thereof. This results in incapacitation of the detection system, either because transmissions in the chosen range of wavelengths no longer pass through the window or dome, or because interference (transmissions with a wavelength outside the chosen range) is allowed to pass through the window or dome.

There is thus a widely recognized need for, and it would be highly advantageous to have, an optical window or dome assembly which would be useable at high supersonic speeds without significant alterations in optical properties.

SUMMARY OF THE INVENTION

According to the present invention there is provided an optical window assembly including: (a) an outer window; (b) an inner window; and (c) a housing, wherein the outer window and the inner window are mounted, the housing holding the
5 outer window and the inner window apart, thereby forming an intervening space between the outer window and the inner window.

According to the present invention there is provided An electro-optical detection system including: (a) an electro-optical payload; and (b) an optical window assembly, for passing, to the electro-optical payload, electromagnetic radiation in at
10 least one wavelength band selected from the group consisting of visible wavelength bands and infrared wavelength bands, while blocking electromagnetic radiation of radio and radar frequencies, the optical window assembly including: (i) an outer window, (ii) an inner window, and (iii) a housing, wherein the outer window and the inner window are mounted, the housing holding the outer window and the inner
15 window apart, thereby forming an intervening space between the outer window and the inner window.

According to the present invention there is provided a mobile platform including: (a) an electro-optical detection system including: (i) an optical window assembly, for admitting to the mobile platform electromagnetic radiation in at least
20 one wavelength band selected from the group consisting of visible wavelength bands and infrared wavelength bands, while blocking electromagnetic radiation of radio and radar frequencies, the optical window assembly including: (A) an outer window, (B) an inner window, and (C) a housing, wherein the outer window and the inner window are mounted, the housing holding the outer window and the inner window apart,
25 thereby forming an intervening space between the outer window and the inner

window.

According to the present invention there is provided a method of detecting, from within a platform moving at a supersonic speed, electromagnetic radiation in at least one wavelength band selected from the group consisting of visible wavelength
5 bands and infrared wavelength bands, including the steps of: (a) providing the platform with an inner window that is transparent in the at least one wavelength band; and (b) thermally insulating the inner window, from an atmosphere external to the platform, in a manner that allows the electromagnetic radiation to reach inner window.

The optical window assembly of the present invention includes two windows,
10 an outer window and an inner window, held apart, and thereby defining an intervening space between the two windows, by being mounted in a housing. Some or all of the surfaces of the windows are coated with an electrically conductive optical coating that passes selected visible and/or infrared bands while blocking electromagnetic interference at radio and/or radar frequencies, or with a heat resistant anti-reflection
15 coating. As used herein the term "electrically conductive" means having a surface resistivity of less than about 50 Ω square, preferably less than about 25 Ω square, and most preferably less than about 5 Ω square. As used herein, the term "heat resistant" means that during the supersonic flight of the platform, the optical transmission of the anti-reflective coating degrades by no more than about 25%. Preferably, the optical
20 transmission of the anti-reflective coating degrades by no more than about 10%. Most preferably, the optical transmission of the anti-reflective coating does not degrade to any perceptible degree.

Preferably, the inner surface of the inner window, i.e., the surface of the inner window that faces away from the outer window, is coated with the optical coating, and
25 the remaining surfaces are coated with the anti-reflection coating. Preferred materials

of the optical coating include doped semiconductors such as doped gallium arsenide and doped germanium.

The primary insulation of the inner window from the heat of the external environment is provided by the intervening space between the two windows. This
5 intervening space preferably is occupied either by vacuum or by a thermally insulating substance. Alternatively, a cooling fluid is circulated through the intervening space to actively cool the inner window.

The windows may be either curved or planar, to conform with the shape of the platform wherein the window assembly is mounted.

10 An electro-optical payload of the present invention includes, in addition to the optical window assembly of the present invention, an electro-optical payload that includes an array of photosensitive elements and a focusing component for focusing, onto the array of photosensitive elements, visible and/or infrared light, in the selected bands, that enters the platform via the window assembly. The payload may also
15 include a mechanism for circulating a cooling fluid through the intervening space of the window assembly.

In a mobile platform of the present invention, the electro-optical detection system is mounted with the outer surface of the outer window flush with the fuselage of the platform. The mobile platform also includes a mechanism for propelling the
20 platform at supersonic speed.

The present invention also includes within its scope a method for detecting external visible and/or infrared radiation from within a moving platform, while that platform moves supersonically. The platform is provided with a window that admits the visible and/or infrared radiation while blocking electromagnetic interference at
25 radio and/or radar frequencies. This window is thermally insulated from the external

atmosphere in a manner that allows the desired visible and/or infrared radiation to reach the inner window. Preferably, this insulating is accomplished by making this window the inner window of the optical window assembly of the present invention.

The present invention successfully addresses the shortcomings of the presently known configurations by providing an optical window or dome assembly configured for use at high supersonic speeds and suited for use as part of an electro optical detection system, for example, an electro optical detection system serving as part of a guidance system of a missile or similar platform.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

FIGs. 1A and 1B are cross sectional views of an optical window assembly and an optical dome assembly, respectively, of the present invention;

15 FIG. 2 is a detailed cross sectional view of the optical window assembly of FIG. 1A showing application of coatings to surfaces thereof;

FIG. 3 is a schematic side view of a missile according to the present invention;

FIG. 4 is a schematic illustration of an electro-optical detection system mounted in the missile of FIG. 3.

20 DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is of an optical window or dome assembly which can be used at high supersonic speeds. Specifically, the present invention can be used to prevent excessive heating of heat sensitive components of the assembly, thereby preserving the optical properties thereof at high supersonic speeds. The invention is further of a mobile platform, such as a guided missile, containing the assembly, of an

25

electro-optical detection system containing the assembly, and of a method, of detecting electromagnetic radiation from within a platform moving at supersonic speed, that uses the assembly.

For purposes of this specification and the accompanying claims, the term “platform” refers to any manned or unmanned vehicle, or any portion thereof, that carries a payload that must receive visible or infrared radiation from its external environment. In the description below, the predominant example of such a platform is a missile. In the present context, "missile" refers to any launchable projectile, but not limited to a launchable projectile carrying an explosive charge. Included in the definition are both self-propelled missiles and those which move primarily due to an initial force applied at launch. This definition specifically includes "rockets" as a lay person commonly uses that term. Missiles referred to herein have as their primary, but not exclusive, purpose homing in on a target, contacting the target and damaging, or more preferably destroying, the target. To this end, missiles are typically equipped with a guidance system, as described hereinabove, and a navigation system capable of adjusting a flight trajectory of the missile so that it accurately impacts the target.

Nevertheless, the scope of the term “platform”, as used herein, also includes other mobile vehicles, or portions thereof, that are required to receive visible or infrared radiation from their external environments. In particular, the scope of the term “platform”, as used herein, includes an external pod attached to a manned aircraft, for example by being suspended from the wing of the manned aircraft. The scope of the term “platform”, as used herein, also includes a drone that is tethered to and towed behind a manned or unmanned aircraft.

The principles and operation of a an optical window or dome assembly according to the present invention may be better understood with reference to the

drawings and accompanying descriptions.

Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other
5 embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

Figures 1A and 1B and 2 show cross sectional views of an optical window or
10 dome assembly **20** adapted for operation at high supersonic speeds in accordance with the teachings of the present invention. Assembly **20** includes a housing **30**. Assembly **20** further includes an outer window or dome **22**, an inner window or dome **24** an intervening space **32** formed between outer window or dome **22** and inner window or dome **24**. Housing **30** holds inner window or dome **24** and outer window or dome **22**
15 and helps define intervening space **32**. Inner window or dome **24** and outer window or dome **22** each have an outer surface **26** and an inner surface **28**. Outer surface **26** of outer window or dome **22** contacts an external atmosphere while assembly **20** travels at high supersonic speeds. Inner surface **28** of outer window or dome **22** outer surface **26** of inner window or dome **24** contact intervening space **32**, such that they do not
20 contact an external atmosphere. Outer surface **26** of inner window or dome **24** is therefore shielded from contact with the external atmosphere by outer window or dome **22** towards which it faces. Inner surface **28** of inner window or dome **24** faces away from the outer window or dome, contacting neither intervening space **32** nor the external atmosphere. This physical shielding protects inner dome or window **24** from
25 excessive heating, for example heating caused by friction with the external

atmosphere when traveling at high supersonic speeds.

In order to provide protection from excessive heating for inner dome or window 24, intervening space 32 is filled by a material characterized by high thermal insulation properties, for example, a gas at atmospheric pressure or a gas at
5 sub-atmospheric pressure. The gas may, for example, be air. Alternatively, a cooling fluid is circulated through intervening space 32.

In order to increase the functionality of inner window or dome 24, it is coated with an optical coating 38 on its inner surface 28. Optical coating 38 is selected to be substantially transparent to radiation at the visible and/or the infrared portion of the
10 electromagnetic spectrum and substantially opaque to radiation at the radio frequency and/or radar frequency portion of the electromagnetic spectrum.

For purposes of this specification and the accompanying claims, the term "excessive heating" is defined as the degree of heating which will interfere with function of an optical coating 38 (as set forth hereinbelow) for example by altering an
15 electrical conductivity thereof or by changing the degree to which the coating absorbs or reflects transmissions of a specific wavelength.

For purposes of this specification and the accompanying claims, the term "conductivity" refers to electrical conductivity.

For purposes of this specification and the accompanying claims, the phrase
20 "substantially transparent" is defined as permitting at least 75%, more preferably at least 85 %, more preferably at least 95 %, more preferably at least 99 %, most preferably approximately 100% transmission of radiation of a specified wavelength.

For purposes of this specification and the accompanying claims, the phrase
25 "visible portion of the electromagnetic spectrum" is defined as the portion of the electromagnetic spectrum with wavelengths between 0.4 microns and 0.8 microns.

The most useful band within this portion of the electromagnetic spectrum is the band with wavelengths between 0.4 microns and 0.7 microns.

For purposes of this specification and the accompanying claims, the phrase "infrared portion of the electromagnetic spectrum" is defined as the portion of the electromagnetic spectrum with wavelengths between 0.8 microns and 100 microns. Particularly useful bands within this portion of the electromagnetic spectrum include the band with wavelengths between 3 and 5 microns and the band with wavelengths between 8 and 14 microns.

For purposes of this specification and the accompanying claims, the phrase "substantially opaque" is defined as absorbing at least 75% of the incident radiation in a specified wavelength band.

For purposes of this specification and the accompanying claims, the term "radio frequency" is defined as frequencies between 10 KHz and 300 GHz.

Optical coating **38** is typically characterized by high conductivity and may be, for example, a doped Gallium Arsenide coat or a doped Germanium coat.

Assembly **20** may employ additional, anti-reflective coating **36** applied over one or more, preferably all of the remaining surfaces of inner **24** and/or outer **22** windows or domes of assembly **20**. Coating **36** functions to decrease the degree to which windows or domes **22** and/or **24** reflect or refract incident radiation, thereby increasing the amount of desired radiation which arrives at an electro-optical payload **34**. Coating **36** is preferably selected heat resistant.

In some cases, assembly **20** includes inner window or dome **24** and outer window or dome **22** which are both planar windows as in Figure 1A. In other cases assembly **20** includes inner window or dome **24** and outer window or dome **22** which are both domes, i.e., curved windows as in Figure 1B.

Assembly **20** is designed for use in a missile **40** (Figure 3). Missile **40** is of the type discussed under “field and background”, and includes a guidance section **42**, a warhead **44**, a propulsion system **46** and one or more flight control surfaces **48** (pictured as fins). Window assembly **20a** or dome assembly **20b** is typically installed
5 in guidance section **42** of missile **40** rendering it ready for operation at high supersonic speeds. Assembly **20** serves as part of an electro-optical detection system of missile **40**, the remainder of the electro-optical detection system being electro-optical payload **34**. In the particular example illustrated, electro-optical payload **34a** receives visible and infrared radiation from outside of missile **40** via window assembly **20a** and
10 electro-optical payload **34b** receives visible and infrared radiation from outside of missile **40** via window assembly **20b**.

Propulsion system **46** is an example of a mechanism for propelling an independently moving platform of the present invention, such as missile **40**, at supersonic speed. In the case of a platform, such as a wing pod, that is attached or
15 tethered to a mother vehicle, the mother vehicle propels the platform at supersonic speed.

The present invention is further embodied by a method of preventing excessive heating of optical coating **38**, while operating at high supersonic speeds, where optical coating **38** is selected to be substantially transparent to radiation at the visible and/or
20 the infrared portion of the electromagnetic spectrum and substantially opaque to radiation at the radio frequency and/or radar frequency portion of the electromagnetic spectrum. The method according to this aspect of the present invention is effected by:
(a) providing assembly **20** which includes: (i) housing **30**; (ii) outer window or dome **22** in contact with an external atmosphere and featuring outer surface **26** and inner

surface 28, outer surface 26 of the outer window or dome 22 facing the external atmosphere, inner surface 28 of the outer window or dome 22 facing away from the external atmosphere; (iii) inner window or dome 24 being held by housing 30 and being shielded from contact with the external atmosphere by outer window or dome 22, inner window or dome 24 featuring outer surface 26 and inner surface 28, outer surface 26 of inner window or dome 24 facing outer window or dome 22, inner surface 28 of inner window or dome 24 facing away from outer window or dome 22; and (iv) intervening space 32 formed between outer window or dome 22 and inner window or dome 24; and (b) applying optical coating 38 on one of the outer surface 26 and the inner surface 28 of the inner window or dome 24, thereby preventing excessive heating of optical coating 38 while operating at the high supersonic speeds.

According to still another aspect of the present invention there is provided an electro-optical detection system comprising assembly 20 and an electro-optical payload.

When assembly 20, as part of an electro-optical detection system, is installed in missile 40 which is in use at high supersonic speed, incident radiation impacts outer surface 26 of outer window 22 (black arrows and stippled arrows; Figure 1A). Interference radiation (black arrows) is blocked by optical coating 38, while visible and/or infrared radiation (stippled arrows) passes through optical coating 38 of inner window 24. This radiation impacts upon the electro-optical payload where it is used by the guidance system to make navigation decisions which allow missile 40 to home in on the target.

For purposes of this specification and the accompanying claims, the term "electro-optical payload" refers to an assembly which includes at least a focusing

component and an array of photosensitive elements, e.g., a charge coupled device (CCD). The focusing component may include, for example, lenses, reflectors, beam splitters, mirrors, and prisms arranged or configured to direct and focus incident radiation to the array of photosensitive elements. The array of photosensitive elements
5 absorbs incident radiation in the form of photons and generates an electrical output, the strength thereof corresponding to the number of photons absorbed. The CCD proportionally transforms the incoming photon signal to an electrical signal.

Figure 4 shows, schematically, an electro-optical detection system **60** of the present invention, including window assembly **20a** and installed within guidance
10 section **42** of missile **40**. As noted above, electro-optical detection system **60** includes both window assembly **20a** and electro-optical payload **34a**. Electro-optical payload **34a** includes a focusing component **62**, represented symbolically as a convex lens, and an array **64** of photosensitive elements. Visible and/or infrared radiation entering missile **40** via window assembly **20a** is focused by focusing component **62** onto array
15 **64**. Note that outer surface **26** of outer window **22** of window assembly **20a** is flush with fuselage **50** of missile **40**. Electro-optical detection system **60** also includes a mechanism for circulating a fluid coolant **58** through intervening space **32** of window assembly **20a**. Specifically, tubing **52** connects intervening space **32** of window assembly **20a**, via ports **55** in housing **30** of window assembly **20a**, to a refrigerator **56**
20 and a pump **54**. Pump **54** circulates coolant **58** through intervening space **32**, and refrigerator **56** cools hot coolant **58** arriving from window assembly **20a**.

Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all
25 such alternatives, modifications and variations that fall within the spirit and broad

scope of the appended claims. All publications cited herein are incorporated by reference in their entirety. Citation or identification of any reference in this section or in any other section of this application shall not be construed as an admission that such reference is available as prior art to the present invention.

WHAT IS CLAIMED IS:

1. An optical window assembly comprising:
 - (a) an outer window;
 - (b) an inner window; and
2. The optical window assembly of claim 1, wherein said outer window includes an outer surface facing away from said inner window and an inner surface facing towards said inner window, wherein said inner window includes an outer surface facing towards said outer window and an inner surface facing away from said outer window, and wherein at least one of said surfaces is coated with an optical coating that is substantially transparent in at least one wavelength band selected from the group consisting of visible wavelength bands and infrared wavelength bands and that is substantially opaque to electromagnetic radiation of radio and radar frequencies.
 - (c) a housing, wherein said outer window and said inner window are mounted, said housing holding said outer window and said inner window apart, thereby forming an intervening space between said outer window and said inner window.
3. The optical window assembly of claim 2, wherein said inner surface of said inner window is coated with said optical coating.

4. The optical window assembly of claim 2, wherein said optical coating is electrically conductive.

5. The optical window assembly of claim 2, wherein said optical coating includes at least one material selected from the group consisting of doped gallium arsenide and doped germanium.

6. The optical window assembly of claim 1, wherein said outer window includes an outer surface facing away from said inner window and an inner surface facing towards said inner window, wherein said inner window includes an outer surface facing towards said outer window and an inner surface facing away from said outer window, and wherein at least one of said surfaces is coated with an anti-reflective coating.

7. The optical window assembly of claim 6, wherein said outer surface of said outer window, said inner surface of said outer window and said outer surface of said inner window are coated with said anti-reflective coating.

8. The optical window assembly of claim 6, wherein said anti-reflective coating is heat resistant.

9. The optical window assembly of claim 1, wherein said intervening space is occupied by a vacuum.

10. The optical window assembly of claim 1, wherein said intervening space is occupied by a thermally insulating substance.

11. The optical window assembly of claim 10, wherein said thermally insulating substance is a gas.

12. The optical window assembly of claim 1, wherein said intervening space is occupied by a coolant.

13. The optical window assembly of claim 1, wherein said windows are planar.

14. The optical window assembly of claim 1, wherein said windows are curved.

15. An electro-optical detection system comprising:

- (a) an electro-optical payload; and
- (b) an optical window assembly, for passing, to said electro-optical payload, electromagnetic radiation in at least one wavelength band selected from the group consisting of visible wavelength bands and infrared wavelength bands, while blocking electromagnetic radiation of radio and radar frequencies, said optical window assembly including:
 - (i) an outer window,
 - (ii) an inner window, and

- (iii) a housing, wherein said outer window and said inner window are mounted, said housing holding said outer window and said inner window apart, thereby forming an intervening space between said outer window and said inner window.

16. The electro-optical detection system of claim 15, wherein said outer window includes an outer surface facing away from said inner window and an inner surface facing towards said inner window, wherein said inner window includes an outer surface facing towards said outer window and an inner surface facing away from said outer window, and wherein at least one of said surfaces is coated with an optical coating that is substantially transparent in at least one of said wavelength bands and that is substantially opaque to said electromagnetic radiation of radio and radar frequencies.

17. The electro-optical detection system of claim 16, wherein said inner surface of said inner window is coated with said optical coating.

18. The electro-optical detection system of claim 15, wherein said intervening space is occupied by a vacuum.

19. The electro-optical detection system of claim 15, wherein said intervening space is occupied by a thermally insulating substance.

20. The electro-optical detection system of claim 15, wherein said intervening space is occupied by a coolant, the electro-optical detection system further

comprising:

- (c) a mechanism for circulating said coolant through said intervening space.

21. The electro-optical detection system of claim 15, wherein said electro-optical payload includes:

- (i) an array of photosensitive elements, and
- (ii) a focusing component for focusing said electromagnetic radiation in said at least one wavelength band onto said array.

22. A mobile platform comprising:

- (a) an electro-optical detection system including:
 - (i) an optical window assembly, for admitting to the mobile platform electromagnetic radiation in at least one wavelength band selected from the group consisting of visible wavelength bands and infrared wavelength bands, while blocking electromagnetic radiation of radio and radar frequencies, said optical window assembly including:
 - (A) an outer window,
 - (B) an inner window, and
 - (C) a housing, wherein said outer window and said inner window are mounted, said housing holding said outer window and said inner window apart, thereby forming an intervening space between said outer window and said inner window.

23. The mobile platform of claim 22, wherein said electro-optical detection system further includes:

- (ii) an electro-optical payload for receiving said electromagnetic radiation in said at least one wavelength band.

24. The mobile platform of claim 23, wherein said electro-optical payload includes:

- (A) an array of photosensitive elements, and
- (B) a focusing component for focusing said electromagnetic radiation in said at least one wavelength band onto said array.

25. The mobile platform of claim 22, wherein said outer window includes an outer surface facing away from said inner window and an inner surface facing towards said inner window, wherein said inner window includes an outer surface facing towards said outer window and an inner surface facing away from said outer window, and wherein at least one of said surfaces is coated with an optical coating that is substantially transparent in at least one of said wavelength bands and that is substantially opaque to said electromagnetic radiation of radio and radar frequencies.

26. The mobile platform of claim 25, wherein said inner surface of said inner window is coated with said optical coating.

27. The mobile platform of claim 22, further comprising:

- (b) a fuselage;

and wherein said outer window includes an outer surface that is substantially flush with said fuselage.

28. The mobile platform of claim 22, further comprising:

(b) a mechanism for propelling the platform at a supersonic speed.

29. A method of detecting, from within a platform moving at a supersonic speed, electromagnetic radiation in at least one wavelength band selected from the group consisting of visible wavelength bands and infrared wavelength bands, comprising the steps of:

(a) providing the platform with an inner window that is transparent in the at least one wavelength band; and

(b) thermally insulating said inner window, from an atmosphere external to the platform, in a manner that allows the electromagnetic radiation to reach said inner window.

30. The method of claim 29, wherein said inner window includes an outer surface and an inner surface, at least one of said surfaces being coated with an optical coating that is substantially transparent in the at least one wavelength band and that is substantially opaque to electromagnetic radiation of radio and radar frequencies.

31. The method of claim 30, wherein said inner surface is coated with said optical coating.

32. The method of claim 29, wherein said insulating is effected by steps including incorporating said inner window in an optical window assembly that further includes:

- (i) an outer window between said external atmosphere and said inner window, and
- (ii) a housing, wherein said outer window and said inner window are mounted, said housing holding said outer window and said inner window apart, thereby forming an intervening space between said outer window and said inner window.

33. The method of claim 32, wherein said outer window includes an outer surface facing towards said external atmosphere and an inner surface facing towards said inner window, wherein said inner window includes an outer surface facing towards said outer window and an inner surface facing away from said outer window, and wherein at least one of said surfaces is coated with an optical coating that is substantially transparent in the at least one wavelength band and that is substantially opaque to said electromagnetic radiation of radio and radar frequencies.

34. The method of claim 33, wherein said inner surface of said inner window is coated with said optical coating.

35. The method of claim 32, wherein said insulating is effected by steps further including providing a vacuum in said intervening space.

36. The method of claim 32, wherein said insulating is effected by steps further including providing a thermally insulating substance in said intervening space.

37. The method of claim 32, wherein said insulating is effected by steps further including circulating a coolant through said intervening space.



Mark M. Friedman
Advocate, Patent Attorney
Beit Samueloff
7 Haomanim
67897 Tel Aviv






Figure 2






FIG. 3

FIG. 4

